



TECHNICAL DATA SHEET

Pack & Seal Putty FR - Fire Retardent

DESCRIPTION

Sylmasta Pack & Seal FR is a fire-retardent, non-setting sealant putty for packing out electrical and cable boxes to prevent the ingress of moisture, sealing around cable runs, blocking holes and making gaskets for extremely uneven faces. Pack & Seal will seal cable holes through walls, metal and most substrates.

Pack & Seal will not set and is easily removed if required. Pack & Seal also seals around all types of pipework and is used for gasketing between uneven surfaces.

Pack & Seal FR is easily visible to indicate where it has been used.

Applications

- · Packing out junction boxes against moisture & dust
- Forming removable cable glands
- Forming removal seal around cable and pipe runs
- · Filling holes against water ingress
- Making gaskets on uneven surfaces

TECHNICAL DATA

Colour	Red
Appearance.	Putty
Standard Temperature Range	-55°C to 120°C
Flammability Rating	Tested to UL94 V0

STORAGE

Pack & Seal should be stored unopened in a cool, dry location and out of direct sunlight. Stored correctly, this grade can offer a minimum 12 month shelf life from its manufacture.

PACKAGING

Code	Description
PUTR/30g	30g Pack
PUTR/500g	500g Pack
PUTR/5kg	5kg Pack

HEALTH & SAFETY

Use of gloves is recommended when using this product. Observe standard industrial hygeine standards and do not eat or drink when handling.